U72 Option Switch Settings (Pulse/MDB/RS232 104U)

Supported bill USD 1, 5 2 Bills.

-		or to a one			1, -									
	FUNCTI	ON	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
Ī	Reject US	SD 1	ON											
\star	Accept US	SD 1	OFF											
	Reject US	SD 5		ON										
*	Accept US	SD 5		OFF										
	Reserv	red			ON									
*	Reserve	ed			OFF									
	High Accep	otance				ON								
*	High Secu					OFF								
	Enable, if fish BA doesn't work						ON							
*	Disable, BA work	ks normally					OFF							
	Disable Bill Rejec BA Stop By 3							ON						
*	Enable Bill Reject BA Stop By 3	t 4 Times						OFF						
	Harness Di								ON					
*	Harness Ei	nable							OFF					
*	Inhibit Active HIGH									ON				
	Inhibit Active LOW									OFF				
	Power On S	tacker									ON			
*	Power On I	Reject									OFF			
	Class Output Dulca	Lo 50 ms										ON		
	Slow Output Pulse	Hi 300 ms										ON		
	East Outsut Dulas	Lo 50 ms										OEE		
*	Fast Output Pulse	Hi 100 ms										OFF		
	Reserve	ed											ON	
\star	Reserved												OFF	
	Reserve	ed												ON
\star	Reserve	ed												OFF

★Manufacture setting

Note: Please reset the bill acceptor after any changes on Dip switch.

U72 USD2(Pulse/MDB/RS232 104U)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
\bigstar	Reserved	ON			
	Reserved	OFF			
\bigstar	Pulse Mode		ON		
	Other Mode		OFF		
\bigstar	1 pulse / USD 1			OFF	OFF
	2 pulse / USD 1			OFF	ON
	4 pulse / USD 1			ON	OFF
	20 pulse / USD 1			ON	ON

[★]Manufacture setting

DIP SWITCHES SETTING: 2(MDB)

	FUNCTION	SW1	SW2	SW3	SW4
\bigstar	Reserved	ON			
	Reserved	OFF			
	Pulse Mode		ON		
\bigstar	Other Mode		OFF		
\bigstar	MDB			OFF	OFF
	RS232 104U			OFF	ON
	Reserved			ON	OFF
	Reserved			ON	ON

★Manufacture setting

Note:(1) Please reset the bill acceptor after any changes on Dip switch. (2)Please open the panel of front, and can see the DIP switch.

Currency Assign Data

Interface Bill value	Pulse	MDB	RS232 104U
BV1	USD 1	USD 1	USD 1
BV2	USD 5	USD 5	USD 5

DIP SWITCHES SETTING : 2(RS232 104U)

	FUNCTION	SW1	SW2	SW3	SW4
\star	Reserved	ON			
	Reserved	OFF			
	Pulse Mode		ON		
\star	Other Mode		OFF		
	MDB			OFF	OFF
\star	RS232 104U			OFF	ON
	Reserved			ON	OFF
	Reserved			ON	ON

[★]Manufacture setting