



## TP70/P5 Protocol for ICT002 / Pulse

**NAD5 Support bill 10、 20、 50、 100、 200 (Namibia)**

### DIP SW SETTING : 1

FUNCTION		SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / NAD 10	OFF	OFF	OFF							
	2 Pulse / NAD 10	OFF	OFF	ON							
	3 Pulse / NAD 10	OFF	ON	OFF							
	4 Pulse / NAD 10	OFF	ON	ON							
	5 Pulse / NAD 10	ON	OFF	OFF							
	10 Pulse / NAD 10	ON	OFF	ON							
	20 Pulse / NAD 10	ON	ON	OFF							
	100 Pulse / NAD 10	ON	ON	ON							
	Fast Output Pulse	Lo=50ms Hi=100ms			ON						
★	Slow Output Pulse	Lo=50ms Hi=300ms			OFF						
	Inhibit level Active Low					ON					
★	Inhibit level Active High					OFF					
★	Accept NAD 10						ON				
	Reject NAD 10						OFF				
★	Accept NAD 20						ON				
	Reject NAD 20						OFF				
★	Accept NAD 50								ON		
	Reject NAD 50								OFF		
★	Accept NAD 100									ON	
	Reject NAD 100									OFF	
★	Accept NAD 200										ON
	Reject NAD 200										OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after any changes on Dip switch.

(2) Dip Switch 1 to 5 are only for Pulse mode.

### DIP SW SETTING : 2

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High (NO)	ON			
Pulse Normal Low (NC)	OFF			
★ Pulse Protocol		ON		
ICT Protocol		OFF		
Straight			ON	
★ Turn Over			OFF	
Manufacture Default				ON
★ System Default				OFF

★ Manufacture setting

Note: (1) Please reset the bill acceptor after any changes on Dip switch

(2) Dip Switches 1 & 3 are only used for pulse protocol.